

## EvoTek™ 2010 P

### Water-Reducing Admixture Powder for Grout and Dry Formulated Concrete Products

#### General Description

Riteks EvoTek™ 2010 P is a high-range water-reducing admixture powder utilizing new and superior polycarboxylate admixture technology for concrete. EvoTek 2010 P is designed to facilitate the placing and finishing of all concrete that is highly flowable and workable with greatly reduced water demand (2 - 40%).

#### Features/Advantages

- Improves surface aesthetics and reduces surface defects and washout
- Improves the quality of concrete by decreasing water-cementitious ratio
- Increases high early and ultimate strengths both compressive and flexural
- Higher durability and increased density
- Reduces damage caused by freezing and thawing
- Minimizes surface bleeding
- Reduces cracking, creep, shrinkage, segregation and increases cohesiveness
- Improves finishability and workability of concrete
- Improves bond strength of concrete to reinforcing steel
- Reduces permeability and salt penetration
- Higher productivity, reduced labor, and reduced curing costs
- Ideally suited for use in self consolidating concrete mixes
- Better finished surfaces than concrete produced with a Viscosity Modifying Admixture

#### Compatibility

EvoTek 2010 P is compatible with all types of Portland cement, class C and F flyash, silica fume, fibers, approved air entraining, and water-reducing admixtures. EvoTek 2010 P can be used in white, colored, and architectural concrete.

TECHNICAL NOTE: EvoTek 2010 P does not contain calcium chloride or any chloride-based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

#### Health & Environmental Data

Please refer to the Safety Data Sheet for complete health, safety and environmental information.

#### Packaging / Shelf Life

25-kg cloth woven bags.

Store in a clean and dry environment. Product should be used within 18 months of delivery.

For additional information on this product, please contact your Riteks Sales Representative.

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. Riteks shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that Riteks, Inc. believes to be reliable. Riteks, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.



415 Interchange St. McKinney, TX 75071

Ph: 972.529.1118 Toll free: 866.288.5121

[www.riteks.com](http://www.riteks.com)