

## NexCrete™ 1210

### Mid-Range Water Reducing Admixture

#### General Description

Riteks NexCrete™ 1210 is a mid-range water-reducing (MRWR) admixture for concrete utilizing polycarboxylate technology. It is designed to facilitate the placing and finishing of ready-mixed concrete that is highly flowable and workable for extended periods of time with normal setting characteristics. NexCrete 1210 is ideally suited for use in self consolidating concrete (SCC) mixes.

#### Features/Advantages

- Improves quality of concrete by decreasing water-cementitious ratio while maintaining slump life during extended mixing times
- Increases compressive and flexural strengths while reducing cracking, creep shrinkage, surface bleeding and segregation
- Improves finishability, workability, pumpability and bond strength to steel
- Reduces damage caused by freezing and thawing

#### Compatibility

NexCrete 1210 is compatible with all types Portland cement, class C and F fly ash, silica fume, fibers, approved air entraining and water-reducing admixtures. NexCrete 1210 can be used in white, colored and architectural concrete.

#### How to Use/Dosage

Mixing: Dosage: Rates will vary depending on the materials used, ambient conditions and the requirements of a specific project. For best results, each admixture must be introduced separately into the concrete mix.

Recommended Dosage Rate: 1 to 8 fluid ounces per 100 pounds of cementitious material. Due to variations in concrete materials, job site conditions and applications, dosages outside of the recommended range may be required. In such cases, contact your local Riteks Construction Chemical Representative.

Note: NexCrete 1210 does not contain calcium chloride or any chloride-based components and is non-corrosive to reinforced, galvanized floor/roof systems or prestressing steel.

#### Specifications / Compliances

Conforms to: ASTM C 494  
Types A, B and D

#### Health & Environmental Data

Please refer to the Safety Data Sheet for complete health, safety and environmental information.

#### Packaging / Shelf Life

5 gallon pail · 55 gallon drum  
Totes · Bulk deliveries

Store between 32° F and 100° F.  
Product should be used within  
12 months of delivery.

For additional information on this product, please contact your Riteks Sales Representative.

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. Riteks shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that Riteks, Inc. believes to be reliable. Riteks, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.



415 Interchange St. McKinney, TX 75071  
Ph: 972.529.1118 Toll free: 866.288.5121  
[www.riteks.com](http://www.riteks.com)