

EvoTek™ Plus

High-Range Water Reducing Admixture

General Description

Riteks EvoTek™ Plus is a faster setting high-range water-reducing (HRWR) admixture for concrete utilizing polycarboxylate technology. It is designed to facilitate the placing and finishing of pre-stressed and precast concrete that is highly flowable and workable with faster setting characteristics and higher early-age strengths. EvoTek™ Plus is ideally suited for use in self consolidating concrete mixes.

EvoTek™ Plus reduces water content (12-40%) needed for a given workability.

Features/Advantages

- Improves quality of concrete by decreasing water-cementitious ratio while maintaining slump life during extended mixing times
- Increases compressive and flexural strengths
- Reduces cracking, creep shrinkage, surface bleeding and segregation
- Improves finishability, workability, pumpability and bond strength to the steel
- Faster Set Times -- works well with slower setting cements
- Faster Early-Age, Tensioning, and Stripping Strengths
- Increased productivity

Application

- Dosage: Rates will vary depending on the materials used, ambient conditions and the requirements of a specific project.
- For best results, each admixture must be introduced separately into the concrete mix.
- EvoTek™ Plus does not contain calcium chloride or any chloride-based components and is non-corrosive to reinforced, galvanized floor/roof systems or prestressing steel.
- Do not use with admixtures containing betanaphthalene sulfonate.

Recommendation

- Dosage Rate: 2 to 12 fluid ounces per 100 pounds of cementitious material.
- Due to variations in concrete materials, job site conditions and applications, dosages outside of the recommended range may be required.
- In such cases, contact your local Riteks Construction Chemical Representative.

Health And Environmental Data

Before handling or using this product please refer to the Safety Data Sheet for complete health, safety and environmental information. Dispose of waste in accordance with local, state and federal regulations

Specifications

Conforms to:

ASTM C 494 Types A and F
AASHTO M 194 Types A and F
CRD C 87 Types A and F

All other Federal and State specifications

Compatibilities

EvoTek™ Plus is compatible with all types Portland cement, class C & F fly ash, silica fume, fibers, approved air entraining & water reducing admixtures. EvoTek™ Plus can be used in white, colored and blended cements.

Packaging & Storages

5 gallon pail | 55 gallon drum
Totes | Bulk deliveries

Store between 35° F & 100° F.
Product should be used within 12 months of delivery.



Scan to Request a Sample
[281.569.3500](tel:281.569.3500)
service@riteks.com