

HydraStop™ P

Hydration Stabilizer



General Description

Concrete starts its hydration reaction from the time the dry cement has initial contact with the batch water. Extended haul times, excess drum revolutions, temperature and time delays can cause concrete to perform substandard to its intended application.

HydraStop P can be used to offset these adverse factors and produce acceptable concrete in these conditions. HydraStop P is especially helpful in the summer months when hydration is accelerated due to higher ambient and mix temperatures.

Advantages

- Ability to service jobsites at extended travel times from mixing plant
- Helps maintain slump and proper set times of freshly produced concrete over extended haul times and increased ambient temperatures.
- Aids in controlling concrete temperature when a maximum mix temperature is specified.
- Concrete performance properties are still maintained while exceeding the requirements of ASTM, AASHTO and CRD specifications

Procedure for Use

Follow these instructions carefully:

- After concrete has been thoroughly mixed, determine temperature of the concrete.
- Calculate the dosage per cubic yard using the table on this page.
- After HydraStop P has been added to the concrete; mix truck for 2 minutes at fast mixing speed and 5 minutes at normal mixing speed.

The following chart contains HydraStop P dosage recommendations for extended haul times and jobsite delays. These are recommendations only because materials may vary. It is therefore, recommended that trial batches be run to determine exact dosage requirements.

*Not intended to be used for retardation times longer than chart recommendations. Always dose HydraStop P by the full bag. If calculation is less than a full bag, round up so the dosage is in full bags.

Please consult with your local Riteks technical service representative for further assistance.

Packaging/Storage

5 gallon pail | 55 gallon drum
totes | Bulk deliveries

Store between 32° F & 100° F.
Product should be used within
12 months of delivery.

Health And Environmental Data

Before handling or using this
product please refer to the
Safety Data Sheet for complete
health, safety and
environmental information.
Dispose of waste in accordance
with local, state and federal
regulations



Scan to Request
a Sample
[281.569.3500](tel:281.569.3500)
service@riteks.com

Recommended Dosage Chart Bags of HydraStop P Per Yard of Concrete

Concrete Temperate (F)	Retardation (Hours)				
	0-.5	.5-1.0	1.0-1.5	1.5-2.0	2.0-2.5
100-109°F	0.15	0.15	0.2	0.3	0.3
90-99°F	0.1	0.15	0.15	0.2	0.3
80-89°F	0.1	0.1	0.15	0.2	0.25
70-79°F	0.1	0.1	0.15	0.15	0.2
60-69°F	0.1	0.1	0.15	0.15	0.2

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. RITEKS shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that Riteks, Inc. believes to be reliable. RITEKS, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.

