

NexCrete™ 1200

Non-Chloride Mid-Range Water Reducing Admixture

General Description

Ritek's NexCrete™ 1200 is a non-chloride mid-range water-reducing concrete admixture. NexCrete 1200 is designed to offer: Superior workability and finishability, increased compressive and flexural strength (both initial and ultimate) with lower water-cement ratio and normal set times throughout the whole dosage range. NexCrete 1200 does not contain calcium chloride or any chloride-based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

Primary Applications

NexCrete™ 1200 can be used in all concrete applications where ease of placement, normal set times, and increased workability are desired. NexCrete 1200 is used in all flatwork, curb mixes and walls. NexCrete 1200 is compatible with a wide range of cements, fly ashes and aggregates.

NexCrete 1200 provides concrete with lower permeability, little or no bleeding and greater workability at the surface.

- Increased pumpability
- Reduced segregation of mix; even with very high slumps
- Increased relative durability to freezing and thawing
- Superior finishing characteristics for flatwork, walls, curb and tilt-up
- Better retention of slump than conventional water-reducers

How to Use / Dosage

Mixing: NexCrete 1200 can be added with the initial batch water but delayed addition will generally result in optimum water reduction. Dosage: Rates will vary depending on the materials used, ambient conditions and the requirements of a specific project.

Recommended dosage rate: 3 to 12 fl. oz. per 100 lbs. of cementitious material.

Due to variations in concrete materials, job site conditions and applications, dosages outside of the recommended range may be required. In such cases, contact your local Ritek's Construction Chemical Representative.

Features/Advantages

- Increased pumpability
- Reduced segregation of mix; even with very high slumps
- Increased relative durability to freezing and thawing
- Superior finishing characteristics for flatwork, walls, curb and tilt-up
- Better retention of slump than conventional water-reducers

Compatibilites

EvoTek 2000 is compatible with all types Portland cement, class C & F fly ash, silica fume, fibers, approved air entraining & water-reducing admixtures. EvoTek 2000 can be used in white, colored and architectural

Packaging/Storage

5 gallon pail • 55 gallon drum
Totes • Bulk deliveries

Store between 32° F & 100° F. Product should be used within 12 months of delivery.

Health and Environmental Data

Before handling or using this product please refer to the Safety Data Sheet for complete health, safety and environmental information. Dispose of waste in accordance with local, state and federal regulations.

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. Ritek's shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that Ritek's, Inc. believes to be reliable. Ritek's, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.



Headquarters:

11917 Cutten Road Houston, TX 77066
Ph: [281] 569-3500 • Fax: [281] 569-3508
www.riteks.com

Dallas Plant :

415 Interchange Street McKinney, TX 75071