



## SYAD™ 40

### Set Retarding Water Reducing Admixture

#### General Description

Riteks SYAD™40 is a set retarding water reducing multi-component admixture for concrete. It is designed to facilitate the placing and finishing of concrete while providing control over the set time. SYAD 40 improves pumpability of concrete and is especially beneficial during hot weather concreting operations when control of setting time and maintenance of placeable consistency are essential. SYAD 40 provides superior finishability on all flatwork and pre-cast surfaces.

#### Features/Advantages

SYAD 40 provides variable control of setting time based on dosage rate and improves quality of concrete by decreasing water-cement ratio while maintaining slump life during extended mixing times. SYAD 40 increases compressive and flexural strengths. SYAD 40 reduces cracking, shrinkage, surface bleeding and segregation. SYAD 40 resists damage caused by freezing and thawing and aids in preventing cold joints and reduces thermal cracking in mass pour concrete.

#### How to Use / Dosage

Dosage: Rates will vary depending on the materials used, ambient conditions and the requirements of a specific project. SYAD 40 is normally added to the concrete mix at the following dosage rates as a function of temperature.

Dosage per 100 lbs. of cement: 70°F - 3 fl oz. 75°F - 4 fl oz. 80°F - 5 fl oz. 85° F and up - 6 fl oz.

Due to variations in concrete materials, job site conditions and applications, dosages outside of the recommended range may be required. In such cases, contact your local Riteks Construction Chemical Representative. Note: SYAD 40 does not contain calcium chloride or any chloride-based components and is non-corrosive to reinforced, galvanized floor/roof systems or prestressing steel.

#### Conforms to:

- ASTM C 494 Type B and D

#### Packaging/Storage

5 gallon pail • 55 gallon drum  
Totes • Bulk deliveries

Store between 32° F & 100° F. Product should be used within 12 months of delivery.

#### Health and Environmental Data

Before handling or using this product please refer to the Safety Data Sheet for complete health, safety and environmental information. Dispose of waste in accordance with local, state and federal regulations.

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. Riteks shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection there with. The information provided herein is based on technical data that Riteks, Inc. believes to be reliable. Riteks, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.



#### Headquarters:

11917 Cutten Road Houston, TX 77066  
Ph: [281] 569-3500 • Fax: [281] 569-3508  
[www.riteks.com](http://www.riteks.com)

#### Dallas Plant :

415 Interchange Street McKinney, TX 75071